

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 February 2001 (08.02.2001)


PCT

(10) International Publication Number
WO 01/09543 A1

- (51) International Patent Classification⁷: **F16L 19/065** (74) Agents: **HÅMSØ, Eivind et al.**; Håmsø Patentbyrå Ans, Box 171, N-4302 Sandnes (NO).
- (21) International Application Number: **PCT/NO00/00214**
- (22) International Filing Date: **22 June 2000 (22.06.2000)** (81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: **Norwegian**
- (26) Publication Language: **English**
- (30) Priority Data:
19993437 12 July 1999 (12.07.1999) NO
- (71) Applicant (*for all designated States except US*): **BAKKE TECHNOLOGY AS [NO/NO]**; Opstadveien 11, N-4330 Ålgård (NO).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **BAKKE, Stig** [NO/NO]; Nesjaberget 9, N-4330 Ålgård (NO).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: **CONNECTOR AND METHOD OF USE OF THE CONNECTOR**



Sub A1 (57) Abstract: A connector (16, 24, 18, 20) for the connection of a pipe end portion of coiled tubing (10) comprises means (22) for connecting a piece of downhole equipment, and is formed by three separate parts that can be screwed together two and two, of which a radially inner shrinkable adapter sleeve (20) compressively surrounded by an elongate outer adapter and connector sleeve (18) ensures the securing of the end portion of the coiled tubing (10), whereas a freely projecting, internally threaded end portion of the outer sleeve (18) ensures the connection to the remaining part (16, 24) of the connector in the screwing together. To obtain a connector which, besides exhibiting superior tensile, flexural and compressive strength properties, is also well suited to absorb torques applied, the inner shrinkable adapter sleeve (20), which has an external jacket surface of an axially conical extent, is provided with external threads, complementarily matched by the internal threads of the outer adapter and connector sleeve (18), which are formed in the bore-defining inner circumferential surface, which has a conical extent in the axial direction, its conicity complementarily corresponding to the externally conical extent of the inner adapter sleeve (20).

WO 01/09543 A1